



WIRING	INPUT		OUTPUT		SHAFT ROTATION TO INCREASE VOLTAGE	TERMINAL CONNECTIONS		
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD		FOR INCREASING VOLTAGE AS VIEWED FROM ROTOR END		
				MAX. AMPS	MAX. KVA	INPUT	OUTPUT	
THREE PHASE OPEN DELTA	120	50/60	0-140	50	12.1	CW	2-1-2	3-1-3

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS #				UNITS		TITLE: SPEC. CONTROL DRAWING		
DECIMALS	HOLES	ANGLES	DRAFT	IN	MM	TYPE: 5011-2D		
.XX	.002	1°	1-1/2°					
MATERIAL:				ALL DIMENSIONS APPLY AFTER PLATING				
DRAWN BY		DATE	FIRST USED ON	DO NOT SCALE DWG.	CUSTOMER APPROVAL		DATE	
TIM RAU		12/14/95						
CHECKER	DATE	WEIGHT APPROX.	CODE IDENT. NO.	DWG. NO.				
		134 LBS.	83008	031-6015				
ENGINEER	DATE	SCALE	SHEET	DWG. NO.				
		.50=1	1 OF 1	031-6015				