

BLP8G10S-270PW

Power LDMOS transistor

Rev. 2 — 1 October 2015

AMMPLION

Product data sheet

1. Product profile

1.1 General description

270 W LDMOS packaged symmetric Doherty power transistor for base station applications at frequencies from 700 MHz to 900 MHz.

Table 1. Typical performance

Typical RF performance at $T_{case} = 25\text{ °C}$ in a Doherty application test circuit. $V_{DS} = 28\text{ V}$; $I_{Dq} = 500\text{ mA}$ (main); $V_{GS(amp)peak} = 0.5\text{ V}$, unless otherwise specified.

Test signal	f	V_{DS}	$P_{L(AV)}$	G_p	η_D	ACPR
	(MHz)	(V)	(dBm)	(dB)	(%)	(dBc)
1-carrier W-CDMA	716 to 768	28	47.5	17.3	46	-35 [1]

[1] Test signal: 1-carrier W-CDMA; 3GPP test model 1; 64 DPCH; PAR = 9.65 dB at 0.01% probability on CCDF per carrier.

1.2 Features and benefits

- Excellent ruggedness
- High-efficiency
- Low thermal resistance providing excellent thermal stability
- Lower output capacitance for improved performance in Doherty applications
- Designed for low memory effects providing excellent digital pre-distortion capability
- Internally matched for ease of use
- Integrated ESD protection
- Bias through video leads
- Compliant to Directive 2002/95/EC, regarding Restriction of Hazardous Substances (RoHS)

1.3 Applications

- RF power amplifiers for base stations and multi carrier applications in the 700 MHz to 900 MHz frequency range

2. Pinning information

Table 2. Pinning

Pin	Description	Simplified outline	Graphic symbol
1, 2	gate		 aaa-008888
3, 6	bias/video decoupling		
4, 5	drain		
7	source [1]		

[1] Connected to flange.

3. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
BLP8G10S-270PW	HSOP6F	plastic, heatsink small outline package; 6 leads (flat)	SOT1221-2

4. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	drain-source voltage		-	65	V
$V_{GS(amp)main}$	main amplifier gate-source voltage		-0.5	+13	V
$V_{GS(amp)peak}$	peak amplifier gate-source voltage		-0.5	+13	V
T_{stg}	storage temperature		-65	+150	°C
T_j	junction temperature	[1]	-	225	°C

[1] Continuous use at maximum temperature will affect the reliability, for details refer to the on-line MTF calculator.

5. Thermal characteristics

Table 5. Thermal characteristics

Symbol	Parameter	Conditions	Typ	Unit
$R_{th(j-c)}$	thermal resistance from junction to case	$V_{DS} = 28\text{ V}; I_{Dq} = 650\text{ mA (main)};$ $V_{GS(amp)peak} = 0.5\text{ V}; T_{case} = 80\text{ °C};$		
		$P_L = 56\text{ W}$	0.50	K/W
		$P_L = 89\text{ W}$	0.43	K/W

6. Characteristics

Table 6. DC characteristics

Per section; $T_j = 25\text{ °C}$ unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$V_{(BR)DSS}$	drain-source breakdown voltage	$V_{GS} = 0\text{ V}; I_D = 2.25\text{ mA}$	65	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	$V_{DS} = 10\text{ V}; I_D = 225\text{ mA}$	1.5	1.9	2.3	V
V_{GSq}	gate-source quiescent voltage	$V_{DS} = 28\text{ V}; I_D = 1000\text{ mA}$	1.7	2.1	2.5	V
I_{DSS}	drain leakage current	$V_{GS} = 0\text{ V}; V_{DS} = 28\text{ V}$	-	-	1.4	μA
I_{DSX}	drain cut-off current	$V_{GS} = V_{GS(th)} + 3.75\text{ V};$ $V_{DS} = 10\text{ V}$	-	37.5	-	A
I_{GSS}	gate leakage current	$V_{GS} = 11\text{ V}; V_{DS} = 0\text{ V}$	-	-	140	nA
g_{fs}	forward transconductance	$V_{DS} = 10\text{ V}; I_D = 11.25\text{ mA}$	-	14	-	S
$R_{DS(on)}$	drain-source on-state resistance	$V_{GS} = V_{GS(th)} + 3.75\text{ V};$ $I_D = 7875\text{ mA}$	-	90	148	$\text{m}\Omega$

Table 7. RF characteristics

Test signal: 1-carrier W-CDMA; 3GPP test model 1; 64 DPCH; PAR = 9.65 dB at 0.01 % probability on the CCDF per carrier; $f_1 = 718.5\text{ MHz}; f_2 = 765.5\text{ MHz}$; RF performance at $V_{DS} = 28\text{ V}; I_{Dq} = 2000\text{ mA}$ (main); $T_{case} = 25\text{ °C}$; unless otherwise specified; in a class AB production test circuit at frequencies from 716 MHz to 768 MHz.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
G_p	power gain	$P_{L(AV)} = 56\text{ W}$	19	20	-	dB
RL_{in}	input return loss	$P_{L(AV)} = 56\text{ W}$	-	-16	-12	dB
η_D	drain efficiency	$P_{L(AV)} = 56\text{ W}$	25	29	-	%
ACPR	adjacent channel power ratio	$P_{L(AV)} = 56\text{ W}$	-	-38	-33	dBc

Table 8. RF characteristics

Test signal: pulsed RF; $f_1 = 718.5\text{ MHz}; f_2 = 756.5\text{ MHz}; t_p = 10\text{ ms}; \delta = 10\%$; RF performance at $V_{DS} = 28\text{ V}; I_{Dq} = 2000\text{ mA}$ (main); $T_{case} = 25\text{ °C}$; unless otherwise specified; in a class-AB narrow band production circuit.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$P_{L(3dB)}$	output power at 3 dB gain compression		315	365	-	W

7. Application information

7.1 Application circuit




Table 9. List of components

See [Figure 15](#) for component layout.


Component	Description	Value	Remarks
C1, C2, C3, C4, C14, C19, C25	multilayer ceramic chip capacitor	82 pF	ATC 600F
C5, C6, C16, C17, C22, C23, C26	multilayer ceramic chip capacitor	10 μF	Murata: GRM32ER71H106KA12
C7, C8, C9, C10	multilayer ceramic chip capacitor	15 pF	ATC 600F
C11, C12	multilayer ceramic chip capacitor	5.6 pF	ATC 600F
C13	multilayer ceramic chip capacitor	1.8 pF	ATC 600F
C15, C21	multilayer ceramic chip capacitor	1 μF	Murata: GRM31CR72A105KA01L
C18, C24	electrolytic capacitor	2200 μF	Multicomp: MCGPR35V228M16X32
L1, L2, L3, L4	chip ferrite bead	-	Murata; BLE32PN300SN1L
Q1, Q2	transistor	-	Fairchild: MMBT2222
R1	resistor	50 Ω	Panasonic: ERJ-L14KF50MU
R2, R4	resistor	1.1 k Ω	Vishay Dale

Table 9. List of components
See [Figure 15](#) for component layout.

Component	Description	Value	Remarks
R3	resistor	1.2 kΩ	Vishay Dale
R5	resistor	3.9 kΩ	Vishay Dale
X1	hybrid coupler	3 dB, 90°	Anaren: X3C07P1-03S


7.2 Graphical data measured at frequency band from 716 MHz to 768 MHz

7.2.1 Pulsed CW




7.2.2 1-Carrier W-CDMA

PAR = 9.7 dB per carrier at 0.01 % probability on the CCDF; 3GPP test model 1 with 64 DPCH (100 % clipping).




$V_{DS} = 28\text{ V}$; $I_{Dq} = 500\text{ mA}$; $V_{GS(amp)peak} = 0.50\text{ V}$.
 (1) $f = 716\text{ MHz}$
 (2) $f = 742\text{ MHz}$
 (3) $f = 768\text{ MHz}$

Fig 4. Power gain and drain efficiency as function of output power; typical values




$V_{DS} = 28\text{ V}$; $I_{Dq} = 500\text{ mA}$; $V_{GS(amp)peak} = 0.50\text{ V}$.
 (1) $f = 716\text{ MHz}$
 (2) $f = 742\text{ MHz}$
 (3) $f = 768\text{ MHz}$

Fig 5. Adjacent channel power ratio (5 MHz) as a function of output power; typical values



$V_{DS} = 28\text{ V}$; $I_{Dq} = 500\text{ mA}$; $V_{GS(amp)peak} = 0.50\text{ V}$.
 (1) $f = 716\text{ MHz}$
 (2) $f = 742\text{ MHz}$
 (3) $f = 768\text{ MHz}$

Fig 6. Peak-to-average power ratio as a function of output power; typical values




$V_{DS} = 28\text{ V}$; $I_{Dq} = 500\text{ mA}$; $V_{GS(amp)peak} = 0.50\text{ V}$.
 (1) $f = 716\text{ MHz}$
 (2) $f = 742\text{ MHz}$
 (3) $f = 768\text{ MHz}$

Fig 7. Input return loss as a function of output power; typical values


7.2.3 2-Carrier W-CDMA

PAR = 8.4 dB at 0.01 % probability on the CCDF; 3GPP test model 1 with 64 DPCH (46 % clipping).




$V_{DS} = 28\text{ V}$; $I_{Dq} = 500\text{ mA}$; $V_{GS(amp)peak} = 0.50\text{ V}$.
 (1) $f = 716\text{ MHz}$
 (2) $f = 742\text{ MHz}$
 (3) $f = 768\text{ MHz}$

Fig 8. Power gain and drain efficiency as function of output power; typical values



$V_{DS} = 28\text{ V}$; $I_{Dq} = 500\text{ mA}$; $V_{GS(amp)peak} = 0.50\text{ V}$.
 (1) $f = 716\text{ MHz}$
 (2) $f = 742\text{ MHz}$
 (3) $f = 768\text{ MHz}$



Fig 9. Adjacent channel power ratio (5 MHz) and adjacent channel power ratio (10 MHz) as function of output power; typical values




$V_{DS} = 28\text{ V}$; $I_{Dq} = 500\text{ mA}$; $V_{GS(amp)peak} = 0.50\text{ V}$.
 (1) $f = 716\text{ MHz}$
 (2) $f = 742\text{ MHz}$
 (3) $f = 768\text{ MHz}$

Fig 10. Input return loss as a function of output power; typical values

7.2.4 CW



7.2.5 2-Tone VBW



8. Test information

8.1 Ruggedness in Doherty operation

The BLP8G10S-270PW is capable of withstanding a load mismatch corresponding to VSWR = 10 : 1 through all phases under the following conditions: $V_{DS} = 28\text{ V}$; $I_{Dq} = 2000\text{ mA}$; $f = 719\text{ MHz}$. Test signal: 1-carrier W-CDMA; $P_L = 85\text{ W}$ (5 dB OBO); 100 % clipping

8.2 Impedance information

Table 10. Typical impedance of main or peak device

Measured load-pull data of main device; $I_{Dq} = 700\text{ mA}$ (main); $V_{DS} = 28\text{ V}$; pulsed CW ($t_p = 100\text{ }\mu\text{s}$; $\delta = 10\%$).

f (MHz)	Z_S [1] (Ω)	Z_L [1] (Ω)	P_L [2] (W)	η_D [2] (%)	G_p [2] (dB)
Maximum power load					
728	3.1 – j0.8	1.3 – j2.0	261.2	60.0	17.3
748	3.1 – j1.1	1.3 – j1.9	258.6	60.6	17.3
768	3.1 – j1.4	1.3 – j1.9	252.1	60.3	17.4
869	4.4 – j2.2	1.4 – j2.6	240.6	60.1	17.3
880	4.7 – j2.3	1.3 – j2.6	237.3	59.9	17.3
894	5.1 – j2.0	1.3 – j2.6	235.9	60.5	17.3
Maximum drain efficiency load					
728	3.1 – j0.8	3.5 – j1.1	164.7	73.4	20.0
748	3.1 – j1.1	3.5 – j0.7	150.3	73.2	20.2
768	3.1 – j1.4	3.2 – j0.7	150.3	72.2	20.0
869	4.4 – j2.2	2.4 – j1.0	141.9	71.4	19.8
880	4.7 – j2.3	2.4 – j1.0	136.7	70.4	19.7
894	5.1 – j2.0	2.0 – j1.4	155.9	70.3	19.3

[1] Z_S and Z_L defined in [Figure 14](#).

[2] At 3 dB gain compression.




Fig 14. Definition of transistor impedance

8.3 Test circuit




Table 11. List of components

See [Figure 15](#) for component layout.

Component	Description	Value	Remarks
C1, C3, C6, C9, C12	multilayer ceramic chip capacitor	82 pF	[1] ATC 800B
C2	multilayer ceramic chip capacitor	180 pF	[1] ATC 800B
C4, C7, C10, C13	multilayer ceramic chip capacitor	1 μF	[2] Murata
C5, C8, C11, C14	multilayer ceramic chip capacitor	10 μF, 50 V	[2] Murata
C15, C16	electrolytic capacitor	2200 μF, 63 V	
R1	resistor	5 kΩ	SMD 1206

[1] American Technical Ceramics type 800B or capacitor of same quality.

[2] Murata or capacitor of same quality.

9. Package outline

HSOP6F: plastic, heatsink small outline package; 6 leads(flat)

SOT1221-2




Fig 16. Package outline SOT1221-2 (HSOP6F)

10. Handling information

CAUTION



This device is sensitive to ElectroStatic Discharge (ESD). Observe precautions for handling electrostatic sensitive devices.

Such precautions are described in the *ANSI/ESD S20.20*, *IEC/ST 61340-5*, *JESD625-A* or equivalent standards.

11. Abbreviations

Table 12. Abbreviations

Acronym	Description
3GPP	3rd Generation Partnership Project
AM	Amplitude Modulation
CCDF	Complementary Cumulative Distribution Function
CW	Continuous Wave
DPCH	Dedicated Physical CHannel
ESD	ElectroStatic Discharge
LDMOS	Laterally Diffused Metal-Oxide Semiconductor
MTF	Median Time to Failure
OBO	Output Back-Off
PAR	Peak-to-Average Ratio
PM	Phase Modulation
SMD	Surface Mounted Device
VBW	Video Bandwidth
VSWR	Voltage Standing Wave Ratio
W-CDMA	Wideband Code Division Multiple Access

12. Revision history

Table 13. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
BLP8G10S-270PW v.2	20151001	Product data sheet	-	BLP8G10S-270PW v.1
Modifications:	<ul style="list-style-type: none"> The format of this document has been redesigned to comply with the new identity guidelines of Ampleon Legal texts have been adapted to the new company name where appropriate 			
BLP8G10S-270PW v.1	20150917	Product data sheet	-	-

13. Legal information

13.1 Data sheet status

Document status ^{[1][2]}	Product status ^[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.ampleon.com>.

13.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Ampleon does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Ampleon sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Ampleon and its customer, unless Ampleon and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Ampleon product is deemed to offer functions and qualities beyond those described in the Product data sheet.

Ampleon product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Ampleon and its suppliers accept no liability for inclusion and/or use of Ampleon products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Ampleon makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Ampleon products, and Ampleon accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Ampleon product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Ampleon does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Ampleon products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Ampleon does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Ampleon products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.ampleon.com/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Ampleon hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Ampleon products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

13.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Ampleon does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Ampleon takes no responsibility for the content in this document if provided by an information source outside of Ampleon.

In no event shall Ampleon be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Ampleon's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Ampleon.

Right to make changes — Ampleon reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Ampleon products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an

Non-automotive qualified products — Unless this data sheet expressly states that this specific Ampleon product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Ampleon accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Ampleon' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Ampleon' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Ampleon for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Ampleon' standard warranty and Ampleon' product specifications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

13.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

Any reference or use of any 'NXP' trademark in this document or in or on the surface of Ampleon products does not result in any claim, liability or entitlement vis-à-vis the owner of this trademark. Ampleon is no longer part of the NXP group of companies and any reference to or use of the 'NXP' trademarks will be replaced by reference to or use of Ampleon's own trademarks.

14. Contact information

For more information, please visit: <http://www.ampleon.com>

For sales office addresses, please visit: <http://www.ampleon.com/sales>

15. Contents

1 **Product profile** 1

1.1 General description 1

1.2 Features and benefits 1

1.3 Applications 1

2 **Pinning information** 2

3 **Ordering information** 2

4 **Limiting values** 2

5 **Thermal characteristics** 2

6 **Characteristics** 3

7 **Application information** 4

7.1 Application circuit 4

7.2 Graphical data measured at frequency band from 716 MHz to 768 MHz 5

7.2.1 Pulsed CW 5

7.2.2 1-Carrier W-CDMA 6

7.2.3 2-Carrier W-CDMA 7

7.2.4 CW 8

7.2.5 2-Tone VBW 8

8 **Test information** 9

8.1 Ruggedness in Doherty operation 9

8.2 Impedance information 9

8.3 Test circuit 10

9 **Package outline** 11

10 **Handling information** 12

11 **Abbreviations** 12

12 **Revision history** 12

13 **Legal information** 13

13.1 Data sheet status 13

13.2 Definitions 13

13.3 Disclaimers 13

13.4 Trademarks 14

14 **Contact information** 14

15 **Contents** 15

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© Ampleon Netherlands B.V. 2016. All rights reserved.

For more information, please visit: <http://www.ampleon.com>
 For sales office addresses, please visit: <http://www.ampleon.com/sales>

Date of release: 1 October 2015
 Document identifier: BLP8G10S-270PW